



STANDARD FEATURES

- Heavy-duty mild steel construction
- "Modular" design
- Big Bag 1000x1000 mm
height 1000 mm
capacity 1000 Kg
- Bag lift spreader
- Suitable for minijet M 379 installation

STANDARD OPTIONS

- Electric hoist (2000 kg) with:
 - 1.5/6 m/min lift speed
 - Pendant controls
- Power trolley(3.5/14m/min travel speed)
- Containment hopper/access box with:
 - 1200X1200 top opening (big bag housing)
 - Bag spout access doors
 - Vent connection
- Pneumatic bag agitators with:
 - (5) air cylinder
 - Solenoids to control agitation
- Customize (enlarged) bottom frame for high volume container or transporter

SPECIFICATIONS

- 5.5 bar clean-dry-air at correct pressure dew point
- 400V / 3Ph / 50Hz for hoist & trolley
- supplies 24Vdc
- Weight= 1570 kg

ADDITIONAL OPTIONS

- Custom units for application
- Transition hoppers
- Big Bag dimension:
950x950 - 1050x1050 mm
capacity 500÷2000 Kg
- Built-in dust collector with pneumatic cleaning system
- Stainless contact surfaces and structure (SS304/316)
- Fan
- Control panel
- Conform to Atex 94/9/CE zone 20/21 - 20/22
- Suitable in GMP for food and pharmaceutical applications

The Big Bag Unloader with hoist **Nol-Tec M348** allows a safety working during unloading product avoiding dust leaking.

Designed for all kind of Bulk Bags, with or without tail.