

a~70°

| | WEIGHT(Kg) | VOLUME(L) |
|---|------------|-----------|
| 1 | 10 | 30 |
| 2 | 20 | 60 |
| 3 | 50 | 160 |
| 4 | 100 | 320 |
| 5 | 200 | 630 |

| D | H | Ø | A | B | C |
|------|------|-----|------|-----|------|
| 450 | 400 | 150 | 450 | 150 | 550 |
| 550 | 550 | 150 | 550 | 150 | 700 |
| 750 | 800 | 200 | 750 | 200 | 950 |
| 950 | 1000 | 250 | 950 | 250 | 1150 |
| 1200 | 1350 | 250 | 1200 | 250 | 1500 |

a~75°

| D | H | Ø | A | B | C |
|------|------|-----|------|-----|------|
| 400 | 500 | 150 | 400 | 150 | 650 |
| 500 | 700 | 150 | 500 | 150 | 850 |
| 700 | 950 | 200 | 700 | 200 | 1100 |
| 950 | 1200 | 250 | 950 | 250 | 1350 |
| 1100 | 1600 | 250 | 1100 | 250 | 1750 |


STANDARD FEATURES

- Compact Design
- Integral Inner Liner
- Mild Steel Construction
- Pneumatic Wall Shaker (No Mechanical Moving Part Needed)

SPECIFICATIONS

- Air:
 - Clean and dry at correct pressure dew point
 - 5,5 bar minimum
- Electrical: 24 VDC for instrument

OPTIONAL FEATURES

- Stainless steel construction AISI 316/304
- ATEX design 94/9/CE, zone 20/21 and 20/22 

THE FLEX WALL BATCH SCALE **NOL-TEC** IS A HOPPER WITH A RUBBER FLEX WALL THAT ALLOWS DISCHARGING OF MATERIAL LIMITING MATERIAL RESIDUAL.